SAFETY DATA SHEET PROFI-CAR ECO-LINER Page: 1 von 7 26.08.2015



## **SAFETY DATA SHEET**

## PROFI-CAR ECO-LINER

## Section 1: Identification of the substance / mixture and of the company/undertaking

#### 1.1 Product identifier

Product name: ECO-LINER SAE 10W-40

Productcode: 34210

Synonyme:

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Preparation: Engine Oil

1.3 Details of the supplier of the safety data sheet

Company name / contact: PROFI-TECH GmbH

Otto-Lilienthal-Straße 2 88046 Friedrichshafen Tel. +49 7541/40 286-0 Fax +49 7541/40 286-99 info@profi-tech.com

1.4 Emergency telephone number

Emergency number: +49 7541/40 286-0

## **Section 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification under CHIP: This mixture is not classified as hazardous according to Directive 1999/45/EC.

GHS classification:

Serious eye damage/eye irritation: Eye Irrit. 2

Hazardous to the aquatic environment: Aquatic Chronic 3

This mixture is not classified as hazardous according to Regulation (EC) No. 1272/2008.

Classification under CLP

Most important adverse effects:

2.2 Label elements (DSD/DPD)

Label elements under CLP: Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

Hazard statements:

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

# SAFETY DATA SHEET PROFI-CAR ECO-LINER

Page: 2 von 7 26.08.2015



H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.



## Hazard pictograms:

Signal word: Warning

Precautionary statements:

P264 Wash hands thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container to Dispose of contents/containers in accordance with the regulations of waste disposal.

Risk phrases:

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R51 Toxic to aquatic organisms.

R53 May cause long-term adverse effects in the aquatic environment.

Safety phrases:

Precautionary phrases:

#### 2.3 Other hazards

Product can build up a film on the water surface which can inhibit the oxygen exchange. See also sections 11, 12 and 15.

PBT: Not applicable.

## Section 3: Composition / information on ingredients

#### 3.2. Mixtures

Chemical characterization: Additive, mineral oil.

#### Hazardous componants

<u>Hazardous componar</u>	nts:				
EC No	Chemical name	Quantity			
CAS No	Classification				
Index No	GHS classification				
REACH No					
265-157-1	Baseoil - unspecified, Distillates (petroleum), hydrotreated heavy paraffinic	75 - < 80 %			
64742-54-7					
	Asp. Tox. 1; H304				
01-2119484627-25					
276-738-4	6-738-4 Baseoil - unspecified, Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based				
72623-87-1					
	Asp. Tox. 1; H304				
01-2119474889-13					
283-392-8	Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts	1 - < 2.5 %			
84605-29-8	Xi - Irritant, N - Dangerous for the environment R38-41-51-53				
	Skin Irrit. 2, Eye Dam. 1, Aquatic Chronic 2; H315 H318 H411				
01-2119493626-26					
310-154-3	Phenol, dodecyl-, branched	0.1 - < 0.5 %			
	Xi - Irritant, N - Dangerous for the environment R38-41-51-53				
	Skin Irrit. 2, Eye Irrit. 2, Repr. 2, Aquatic Acute 1, Aquatic Chronic 1; H315 H319 H361 H400 H410				
01-2119513207-49					

Page: 3 von 7 26.08.2015



Further Information: The mixture contains either the substance with CAS 265-157-1 or the substance with the CAS 276-738-4. All concentrations are quoted as mass percentages for liquids and volume percentages for gases. Other substances which are not classified as dangerous are contained up to 100 %. Full text of R- and H-phrases: see section 16.

#### Section 4: First aid measures

#### 4.1. Description of first aid measures

Inhalation: Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Skin contact: After contact with skin, wash immediately with plenty of water and soap. Remove contaminated clothing immediatley and dispose off safely. In case of skin irritation, seek medical treatment.

Eye contact: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist.

Swallowing: Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact:

Eye contact:

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

## **Section 5: Fire-fighting measures**

## 5.1. Extinguishing media

Extinguishing media: Carbon dioxide (CO2). Foam. Dry extinguishing powder. Use water spray jet to protect personnel and to cool endangered containers.

#### 5.2. Special hazards arising from the substance or mixture

The formation of combustible vapours is possible at temperatures above: Flash point. Hot product may produce flammable vapours. Can be released in case of fire: Pyrolysis products, toxic. hydrocarbons. Carbon dioxide. Carbon monoxide. Hydrogen sulphide (H2S). Nitrogen oxides (NOx). Phosphorus oxides. Smoke.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: In case of fire: Wear self-contained breathing apparatus. Full protective suit.

Collect contaminated fire extinguishing water separately.

Do not allow entering drains or surface water

## Section 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Provide adequate ventilation as well as local exhaustion at critical locations. Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Conditions to avoid: Inhalation. Do not put any product-impregnated cleaning rags into your trouser pockets. High slip hazard because of leaking or spilled product.

SAFETY DATA SHEET PROFI-CAR ECO-LINER Page: 4 von 7 26.08.2015



#### 6.2. Environmental precautions

Environmental precautions: Prevent spread over a wide area (e.g. by containment or oil barriers). Do not empty into drains. If product enters soil, it will be mobile and may contaminate groundwater.

#### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Reference to other sections: See section 8 & 13.

#### Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: See section 6.1 Avoid contact with skin and eyes. Keep away from sources of ignition. - No smoking. Wash hands before breaks and after work. All work processes must always be designed so that the following is excluded: Generation/formation of mist

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Keep/Store only in original container.

Suitable packaging: Do not store together with: Spontaneous combustion.

#### 7.3. Specific end use(s)

Observe technical data sheet.

#### Section 8: Exposure controls / personal protection

#### 8.1. Control parameters

Hazardous ingredients:

## Exposure limits (EH40)

	CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
Γ	Mixture	Mineral Oil		5		TWA (8 h)	
						STEL (15 min)	

## 8.2 DNEL/PNEC

DNEL/PNEC:.

## 8.3. Exposure controls

Engineering measures: Provide adequate ventilation as well as local exhaustion at critical locations.

Respiratory protection: Take off immediately all contaminated clothing. Wash hands before breaks and after work. Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

Hand protection: Examples of suitable protective gloves from the company KCL GmbH, D-36124 oak cellular, phone +49 (0) 6659 87300, E-mail are: vertrieb@kcl.de with the following specification (test according to EN 374 In full contact / splash contact: Camatril (Item no .: 731; material: nitrile, Minimum coat thickness: 0.33 mm, Breakthrough time: 480 min) Dermatril (Item no .: 740; material: nitrile, Minimum coat thickness: 0.11 mm, Breakthrough time: 30 min) The selected protective gloves have to satisfy the specifications of EU Directive 89/686 / EEC and the resultant standard EN374. The breakthrough times stated above are based on laboratory measurements of KCL to EN374 and are only

SAFETY DATA SHEET PROFI-CAR ECO-LINER Page: 5 von 7

Page: 5 von 7 26.08.2015



Eye protection: Tightly sealed safety glasses. German Industry Norms (DIN) / European Norms (EN): DIN EN 166

Skin protection: The type of personal protection equipment has to be chosen based on the concentration and amount of the dangerous substance at the workplace. For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes). Chemical resistant safety shoes. with lead protection cap. German Industry Norms (DIN) / European Norms (EN): DIN EN 344

Environmental: Technical measures to prevent exposure. Organisational measures to prevent exposure.

## Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

State: liquid

Colour: yellow, brown

Odour: Characteristic

Evaporation

Solubility in water:

Also soluble in:.

Viscosity:

Kinematic viscosity: 13,7 mm<sup>2</sup>/s DIN 51562

Viscosity test method:

Pour point: -42 °C DIN ISO 3016

Boiling point / range°C: > 320 °C

Lower explosion limits: 0,6 vol. %

Upper explosion limits: 6,5 vol. %

Flammability limits %:

Flash point°C: > 250 °C DIN ISO 2592

Vapour pressure:

Relative density: 853 - 863 g/cm3 DIN 53217

VOC g/l:

#### 9.2. Other information

Other information: No further relevant information available.

## Section 10: Stability and reactivity

#### 10.1. Reactivity

Reactivity: See section 9.

## 10.2. Chemical stability

Chemical stability: If product is stored and handled as prescribed it is stable.



#### 10.3. Possibility of hazardous reactions

The formation of combustible vapours is possible at temperatures above: Flash point

#### 10.4. Conditions to avoid

Conditions to avoid: Oxidizing agents, strong.

#### 10.5. Incompatible materials

Materials to avoid: No data available.

#### 10.6. Hazardous decomposition products

Haz. decomp. products: See section 5.3.

## **Section 11: Toxicological information**

## 11.1. Information on toxicological effects

Toxicocinetics, metabolism and distribution There are no data available on the preparation/mixture itself.

Acute toxicity Classification: none. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Irritation and corrosivity Classification: none. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Sensitising effects Classification: none. Frequently or prolonged contact with skin may cause dermal irritation.

Severe effects after repeated or prolonged exposure: Classification: none. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

Carcinogenic/mutagenic/toxic effects for reproduction:

The ingredients in this mixture do not meet the criteria for classification as CMR category 1 or 2.

Specific effects in experiment on an animal: There are no data available on the preparation/mixture itself.

Additional information on tests: Frequently or prolonged contact with skin may cause dermal irritation.

#### **Section 12: Ecological information**

## 12.1. Toxicity

Ecotoxicity values: There are no data available on the preparation/mixture itself. Classification: none. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

#### 12.2. Persistence and degradability

Persistence and degradability: Not easily bio-degradable (according to OECD-criteria). Product is not easily biodegradable. (Data apply to the main component.

## 12.3. Bioaccumulative potential

Bioaccumulative potential: There are no data available on the preparation/mixture itself.

#### 12.4. Mobility in soil

Mobility: There are no data available on the preparation/mixture itself.

#### 12.5. Results of PBT and vPvB assessment

PBT identification: The components in this formulation do not meet the criteria for classification as PBT or vPvB.

SAFETY DATA SHEET PROFI-CAR ECO-LINER Page: 7 von 7 26.08.2015



#### 12.6. Other adverse effects

Other adverse effects:

## Section 13: Disposal considerations

#### 13.1. Waste treatment methods

Advice on disposal: Dispose of waste according to "Kreislaufwirtschafts- und Abfallgesetz (KrW-/AbfG)". Observe mixture permissions according to "Altölverordnung (Waste oil directive)".

Waste disposal: according to EC Directives 75/442/EEC and 91/689/EEC on waste and hazardous waste in their latest versions. According to EAKV, allocation of waste identity numbers/waste descriptions must be carried out in a specific way for every industry and process.

Waste disposal number of waste from residues/unused products: OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils

Classified as hazardous waste: Waste disposal number of used product OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils

Classified as hazardous waste: 130205

Waste disposal number of contaminated packaging: OIL WASTES AND WASTES OF LIQUID FUELS (except edible oils, and those in chapters 05, 12 and 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated engine, gear and lubricating oils Classified as hazardous waste.

Contaminated packaging: Dispose of waste according to applicable legislation. Non-contaminated packages may be recycled. Packing which cannot be properly cleaned must be disposed of.

## **Section 14: Transport information**

No dangerous good in sense of these transport regulations.

## **Section 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

WGK: Water contaminating class (D): 2 - water contaminating

15.2. Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out.

## **Section 16: Other information**

#### 16.1 Other information:

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights.